

Orient X-Cel 36,000 CPH


# An Introduction: Our history


The Printer's House (TPH) Orient group is a diversified group of companies founded in 1946 that is an industry leader in the manufacturing and supply of a host of engineered products from India. A renowned and trusted name globally when it comes to quality manufacturing.


**The Year was 1946**. **K.D. Kohli**, a freedom fighter and newspaperman, started The Printers House (TPH) Orient group. Since then, TPH has carved a formidable reputation as a quality conscious technology driven manufacturer of a number of products. Tph's adherence to global standards has enabled to export its products to more than 60 countries worldwide.


All our products are produced at factories in a 20 acre campus in Delhi NCR. Tph takes pride in being a company of Indian origin, started by an enterprising freedom fighter turned Newspaperman Mr. K.D. Kohli. The TPH Orient group is now a diversified group of companies and a market leader in printing machinery, packaging machinery, printing consumables, engineering services for Defence and aerospace, and solar energy.

However, it is in our humble origins we take solace and hope to continue to grow whilst supplying a product that can match any global standard.









With over 20,000 printing units supplied worldwide TPH enjoys strong relation-ships with some of the most distinguished and reputed commercial printers, publishers, and news houses in the world.



#### **Our distinguished Patrons**





Orient X-Cel is a single width single circumference web-offset press with a speed up-to 36000 copies per hour for high quality newspaper printing, tabloid printing, book printing and semi-commercial products. The printing modules available for Orient X-Cel (36000 copies per hour) are Mono Unit with Integral Reel stand, 3-Colour Satellite, and 4 High Tower.

Acclaimed as one of the finest web offset presses available worldwide, the Orient X-Cel is truly an engineering marvel and a hallmark of quality and engineering excellence.







#### Features:

- Speed 36,000cph
- Shaftless Footprint
- Automatic Colour Registration
- Automatic Ink Pumping
- · Remote Inking

- Brushmist Dampening
- . Pneumatic Controls
- Automatic Reel Changers
- Stacker

## X-Cel 36,000 CPH 4HI tower

## Orient X-Cel 4HI Tower

#### 4 - high Tower

- Hardened and ground bushes in frame for plate and blanket cylinder sleeves.
- Lever-type swing-down ink fountain with overrides for ink fountain roller.
- Dynamically-balanced hard chromium plated plate and blanket cylinders
- On the nose, slit type plate lock-up system.
- Infra red web break detector
- Safety guards.
- Centralized oil pressure lubrication for drive gears.
- Provision for printing 4 colors on both sides of one web, or 2 colors on both sides of two webs, or single colour on both sides of three webs.
- Heavy-duty timer belt drive for 4 stack units.
- On the run manual adjustment for registration of 4 colors on each side of web.
- Motorized running circumferential register for loading side plate cylinders.
- Motorized side register system for both plate cylinders, on the run
- Variable-speed motorized dampening.
- Centralized water circulation system.
- PU Covered ink vibrator rollers
- Narrow gap blanket lock up
- Antiset web transfer grater roller
- Pneumatic on /off for Main impression/Ink feed/Ink form & Damper form.
- Brushmist dampening System
- Cable management system

#### **OPTIONS**

- Heavy duty Compensator
- Pillar clutch on either side of 4-hi
- Automatic grease lubrication for operating side bearing and bushes.
- Centralized water circulation system with chiller
- Dynamically-balanced solid stainless-steel plate and blanket cylinders\*
- T-Bar blanket lock up system
- Spring type lock up system
- Spray dampening system
- AC drive



## X-Cel 36,000 Mono Unit

#### **MONO UNIT:**

- Hardened and ground bushes in frame for plate and blanket cylinder sleeves
- Lever-type swing-down ink fountain with overrides for ink fountain roller
- Dynamically-balanced hard chromium plated plate and blanket cylinders.
- On the nose slit type plate lock up system
- Motorized side register system for both plate cylinders, on the run
- Infra red web break detector
- Safety guards
- Centralized oil pressure lubrication for drive gears
- Provision for printing 2 colors on same side of web (direct litho)
- Variable speed motorized dampening
- Centralized water circulation system. PU Covered ink vibrator rollers. •Narrow gap blanket

lock-up

- Pneumatic on /off for Main impression/Ink feed/Ink form & Damper form
- Brushmist dampening System
- Cable management system

#### **OPTIONS:**

- Motorized running circumferential register for loading side plate register
- Heavy duty compensator
- AC drive
- Reel lifters (pneumatic control)
- Clutch on either side of unit
- Automatic grease lubrication for operating side bearing and bushes
- Auto reel changers
- Centralized water circulation system with chiller
- T-Bar blanket locking system
- Spring type plate lock up system
- Dynamically-balanced solid stainless-steel plate and blanket cylinders\*





## X-Cel 36,000 CPH 3 colour satellite

#### 3 - Colour satellite Unit

- Hardened and ground bushes in frame for plate and blanket cylinder sleeves Lever-type swing-down ink fountain with overrides for ink fountain roller Dynamically-balanced hard chromium plated plate and blanket cylinders

- Stainless steel, balanced main impression cylinder
- On the nose, slit type plate lock-up system

  Motorized side register system for all plate cylinders on the run
- Motorized running circumferential register on two plate cylinders
- Safety guards
- Centralized oil pressure lubrication for drive gears
- Provision for printing 3 colors on one side of web or 2 colors on one side and 1 color on other side of web
- Heavy-duty compensator
- Variable-speed motorized dampening
- Centralized water circulation system
- PU Covered ink vibrator rollers
- Narrow gap blanket lock up
- Pneumatic on /off for Main impression/Ink feed/Ink form & Damper form
- Infra red web break detector
- Brushmist dampening system
- Cable management system

#### **OPTIONS**

- AC drive
- Automatic grease lubrication for operating side bearings Centralized water circulation system with Chiller
- Dynamically-balanced solid stainless- steel plate and blanket cylinders\* T-bar blanket lock up system
- Spring type plate lock up system

### **Orient X-Cel - Technical Specification**

PARTICULAR	CUT OFF					
	508mm	533mm	546mm	560mm	578mm	630mm
Printing Speed	36000Cph	36000Cph	36000Cph	36000Cph	36000Cph	36000Cph
Paper Width	660-889mm	660-889mm	660-889mm	660-889mm	660-889mm	660-889mm
Reel diameter (Max.)	1070mm(42")	1070mm(42")	1070mm(42")	1070mm(42")	1070mm(42")	1070mm(42")
Printing Plate Width	890mm	890mm	890mm	890mm	890mm	890mm
Printing Plate Length Unbent (Slit)	539mm	563mm	577mm	591mm	609mm	661mm
Printing Plate thickness	0.30/0.28mm	0.30/0.28mm	0.30/0.28mm	0.30/0.28mm	0.30/0.28mm	0.30/0.28mm
Rubber Blanket width	889mm	889mm	889mm	889mm	889mm	889mm
Rubber Blanket Length (T-Bar)	556mm	581mm	594mm	608mm	626mm	678mm
Rubber Blanket Length (Narrow)	587mm	602mm	615mm	630mm	651mm	703mm
Rubber Blanket thickness with packing	2.1mm	2.1mm	2.1mm	2.1mm	2.1mm	2.1mm
Rubber Blanket thickness W/O packing	1.7mm	1.7mm	1.7mm	1.7mm	1.7mm	1.7mm
Printing Length Max.(T-Bar)	482mm	507mm	520mm	534mm	552mm	604mm
Printing Length Max (Narrow)	493mm	518mm	531mm	545mm	563mm	615mm
Non-Printing gap(T-Bar)	26mm	26mm	26mm	26mm	26mm	26mm
Non-Printing gap(Narrow)	15mm	15mm	15mm	15mm	15mm	15mm
Paper Grammage(Uncoated)	38-100gm/sqm	38-100gm/sqm	38-100gm/sqm	38-100gm/sqm	38-100gm/sqm	38-100gm/sqm

# Our contact details

The Printers House (P) Ltd 10, Scindia House Connaught Place, New Delhi, India

Tel: +91-11-23313071-73 Fax: +91-11-23310490

Email:tphho@tphorient.com

URL: www.tphorient.com